MATERIAL SA	FETY	DATA SHEET	Г												
This MSDS complies with OSHA'S Hazard Commu				OSHA Form 1	74										
NFPA Rating: Health-1; Flammability-1; Reactivity-0; Special		HMIS Rating: Health-1; Flammability-1; Reactivity-0; Personal Protection-B													
		DOT Hazard Classification: ORM-D Identity (trade name as used on label): CLEAN SLATE													
								Date Prepared: 09/11/01 Prepared By: Tec Service	M	MSDS Number: Revision- 15					
								Information Calls: (800)325-4869 EMERGENCY RESPONSE NUMBER: 1(800)325-4869		NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA					
SECTION 1 - MATERIAL ID	ENTIFIC														
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES	CAS Number	SARA III LIST	OSHA PEL	ACGIH	Carcinogen										
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater) 2-BUTOXYETHANOL*		444 70 0		(ppm) 25	TLV (ppm) 20	Ref. Source **									
2-BUTOXYETHANOL*		111-76-2	Yes*	(skin)	(skin)	d									
ETHANOL		64-17-5	No	1000	1000	d									
ISOBUTANE / PROPANE BLEND		75-28-5	No	800	800	d									
		74-98-6	No	1000	1000	d									
*GLYCOL ETHER															
			+												
SECTION 2 - PHYSICAL	CHEMIC		STICS	I	1	<u>I</u>									
Boiling Point: N/A	Spe	cific Gravity (H2O=1)	: Concenti	rate Only =0.9	85										
Vapor Pressure: PSIG @ 70°F (Aerosols): Max.70	Vap	Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A													
Vapor Density (Air = 1): N/E	Eva	Evaporation Rate (= 1): N/E													
Solubility in Water: Soluble	Wat	Water Reactive: No													
Appearance and Odor: White foam, sassafras fragrance.															
SECTION 3 - FIRE AN	D EXPL	OSION HAZARD D	ATA												
FLAMMABILITY as per USA FLAME PROJECTION TEST	Auto Ig	nition Temperature	Flamm	ability Limits	in Air by %	n Volume:									
(aerosols) NON-FLAMMABLE	0	N/E		: N/E	% UEL										
FLASH POINT AND METHOD USED (non-aerosols): N/A SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing appara		EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide.													
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatu		a 130°F or the containe	er mav ruptu	ire.											
• • •		Y HAZARD DATA													
STABILITY [X] STABLE [] UNSTABLE	AZARDOUS POLYMERIZATION [] WILL [X] WILL NOT														
		Conditions to Avoid: Open flame, welding arcs, heat, sparks.													
Hazardous Decomposition Products: Carbon monoxide, carbon dioxide.															
		HAZARD DATA													
PRIMARY ROUTES OF ENTRY: [X] INHALATION [] ING	ESTION	I [X]SKIN ABSO	ORPTION	[]EYE	[]NOT HA	ZARDOUS									
ACUTE EFFECTS:															
Inhalation: Excessive inhalation of vapors can be harmful & may cau unconsciousness.	ise head	ache, dizziness, asp	hyxia, ane	sthetic effec	s & possible										
Eye Contact: Slight irritation.	Ski	n Contact: Slight in	itation.												
Ingestion: Possible chemical pneumonitis if aspirated into lungs.		- 0													
CHRONIC EFFECTS: None known to humans. Note: some animal di excessively exposed to 2-butoxyethanol.	ata indica	ates some reports of	anemia, li	ver, kidney, l	ung, blood d	amage when									
Medical Conditions Generally Aggravated by Exposure: May ag	naravate	existing eve skin o		niratory con	litions										
		D PROCEDURES													
Eve Contact: Flush with water for 15 minutes. If irritated, seek media															
· · · · · · · · · · · · · · · · · · ·															
Skin Contact: Wash with soap and water. If irritated, seek medical a															
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medi Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses			dical attent	ion											
SECTION 6 - CONTROL				.011.											
Respiratory Protection (specify type): If vapor concentration exce	eds TLV	, use respirator app	roved by N	IOSH / MSH	A for organi	c vapors.									
Protective Gloves: Disposable latex gloves suggested.		Protection: Safet													
Ventilation Requirements: Adequate ventilation to keep vapor cond															
Other Protective Clothing & Equipment: None															
Hygienic Work Practices: Wash with soap and water before handli	ng food.	Remove contaminat	ed clothing] .											
SECTION 7 - PRECAUTION				·											
Stone To Do Token If Motorial to Smilled On Delegandy. Elucidity of															

Steps To Be Taken If Material Is Spilled Or Released: Flush to sewer with water. Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard. Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.

Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. ** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only